

# **QNAP<sup>®</sup>8 MU Copper Naphthenate Concentrate with Mineral Spirits Safety Data Sheet**

**1. IDENTIFICATION Product identifier Product Name** QNAP8 MU Copper Naphthenate Concentrate with Mineral Spirits Other means of identification SDS # NIS-QNAP8MSMU **Registration Number(s)** EPA Reg. No. 64405-17 **UN/ID No** UN1993 Recommended use of the chemical and restrictions on use **Recommended Use** Wood preservative. Details of the supplier of the safety data sheet Manufacturer Address **Nisus Corporation** 100 Nisus Drive Rockford, TN 37853 Emergency telephone number **Company Phone Number** Phone: (800)-264-0870 Fax: (865) 577-5825 INFOTRAC 1-352-323-3500 (International) **Emergency Telephone** 1-800-535-5053 (North America)

# 2. HAZARDS IDENTIFICATION

Emergency Overview This chemical is a product registered by the Environmental Protection Agency and is subject to certain labeling requirements under federal law. These requirements differ from the classification criteria and hazard information required for safety data sheets, and for workplace labels of non-EPA registered chemicals. Please see Section 15 for additional EPA information.

Appearance Dark, green liquid

Physical state Liquid

Odor Pungent, petroleum distillate

#### Classification

Specific target organ toxicity (repeated exposure)	Category 1
Aspiration toxicity	Category 1
Flammable liquids	Category 3

#### Signal Word Danger

#### **Hazard statements**

Causes damage to organs through prolonged or repeated exposure May be fatal if swallowed and enters airways Flammable liquid and vapor

Issue Date: 03-Jun-2021

Revision Date: 05-May-2022

Version 2



#### **Precautionary Statements - Prevention**

Do not breathe dust/fume/gas/mist/vapors/spray Wash face, hands and any exposed skin thoroughly after handling Do not eat, drink or smoke when using this product Keep away from heat/sparks/open flames/hot surfaces. — No smoking Keep container tightly closed Ground/bond container and receiving equipment Use only non-sparking tools Take precautionary measures against static discharge Use explosion-proof equipment Wear protective gloves/protective clothing/eye protection/face protection

#### Precautionary Statements - Response

Get medical advice/attention if you feel unwell IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician Do NOT induce vomiting In case of fire: Use CO2, dry chemical, or foam for extinction

## Precautionary Statements - Storage

Store locked up Store in a well-ventilated place. Keep cool

#### Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

#### Other hazards

Very toxic to aquatic life with long lasting effects

# 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name	CAS No	Weight-%
Copper naphthenate	1338-02-9	60-80
Mineral Spirits	8052-41-3	20-32

\*\*If Chemical Name/CAS No is "proprietary" and/or Weight-% is listed as a range, the specific chemical identity and/or percentage of composition has been withheld as a trade secret.\*\*

# 4. FIRST AID MEASURES

#### Description of first aid measures

Eye Contact	Immediately flush victim's eyes with large quantities of water for at least 15-20 minutes, while holding the eyelids apart. Remove contact lenses if easy to do so. Continue rinsing. Get immediate medical attention.
Skin Contact	Immediately wash skin thoroughly with soap and water for at least 15-20 minutes. Remove contaminated clothing. Get immediate medical attention. Launder clothing before reuse.

Inhalation	Move victim to fresh air and keep at rest in a position that is comfortable. If breathing is difficult, administer oxygen or administer artificial respiration. Get immediate medical attention.
Ingestion	Do NOT induce vomiting. Rinse mouth. Do not give anything by mouth to an unconscious person. Get immediate medical attention.
Most important symptom	ns and effects, both acute and delayed
Symptoms	May be harmful if swallowed. May be harmful in contact with skin. Causes damage to

organs through prolonged or repeated exposure. May be fatal if swallowed and enters

## Indication of any immediate medical attention and special treatment needed

airways.

Notes to Physician Treat symptomatically.

# **5. FIRE-FIGHTING MEASURES**

#### Suitable Extinguishing Media

Use water fog, foam, dry chemical, or carbon dioxide. Cool fire exposed containers and structures with water.

Unsuitable Extinguishing Media A solid stream of water or foam directed into hot, burning liquid can cause frothing.

#### Specific Hazards Arising from the Chemical

Flammable liquid and vapor.

**Hazardous combustion products** Burning may produce carbon monoxide, carbon dioxide, inorganic copper, and other flammable and toxic gases.

#### Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

# 6. ACCIDENTAL RELEASE MEASURES

# Personal precautions, protective equipment and emergency procedures

**Personal Precautions** Evacuate spill area and keep unprotected personnel away. Wear appropriate protective clothing as described in Section 8.

#### Environmental precautions

**Environmental precautions** Avoid release to the environment. See Section 12 for additional Ecological Information.

# Methods and material for containment and cleaning up

Methods for Containment Prevent further leakage or spillage if safe to do so.

Methods for Clean-UpDike and collect liquid or absorb with an inert absorbent and place in appropriate containers<br/>for disposal. Large spills should be removed using a vacuum truck. Wash spill area<br/>thoroughly. Prevent spill from entering sewers and watercourses. Report releases as<br/>required by local, state and federal authorities.

# 7. HANDLING AND STORAGE

## Precautions for safe handling

pants, socks and shoes when handling or applying this product. When applying this product to non-pressure treated wood, blend/spray operators and any individual that applies to product with a brush/roller must wear an organic vapor respirator. Use with adequate ventilation. Wash thoroughly with soap and water after handling. Remove contaminat clothing immediately and wash before reuse. Remove PPE immediately after handlin	Andling Prevent contact with the eyes, skin and clothing. Avoid breathing mists or aerosols. Weat protective clothing and equipment as described in Section 8. Applicators, mixer and other handlers must wear chemical resistant gloves, protective eyewear, long-sleeved shirt, lo pants, socks and shoes when handling or applying this product. When applying this protot to non-pressure treated wood, blend/spray operators and any individual that applies the product with a brush/roller must wear an organic vapor respirator. Use with adequate ventilation. Wash thoroughly with soap and water after handling. Remove contaminated clothing immediately and wash before reuse. Remove PPE immediately after handling. Wash thoroughly after using and change into clean clothing. Keep containers closed whin not in use.	er ong duct
---	--	-------------------

## Conditions for safe storage, including any incompatibilities

Storage Conditions	Store in a cool (between 40°F and 90°F), dry, well-ventilated area away from incompatible materials. Keep out of reach of children and pets. Do not store in direct sunlight. Keep containers tightly closed. Protect from physical damage. Keep in locked storage.
Packaging Materials	Nonrefillable container. Do not reuse containers. Product residues in empty containers can be hazardous. Follow all SDS precautions when handling empty containers.
Incompatible Materials	Oxidizers.

# 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

## Exposure Guidelines

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Copper naphthenate	TWA: 1 mg/m <sup>3</sup> Cu dust and mist	-	IDLH: 100 mg/m <sup>3</sup> Cu dust and
1338-02-9	-		mist
			TWA: 1 mg/m <sup>3</sup> Cu dust and mist
Mineral Spirits	TWA: 100 ppm	TWA: 500 ppm	IDLH: 20000 mg/m <sup>3</sup>
8052-41-3		TWA: 2900 mg/m <sup>3</sup>	Ceiling: 1800 mg/m <sup>3</sup> 15 min
		(vacated) TWA: 100 ppm	TWA: 350 mg/m <sup>3</sup>
		(vacated) TWA: 525 mg/m <sup>3</sup>	

## Appropriate engineering controls

Engineering Controls	Use with adequate general or local exhaust ventilation to maintain exposure levels below the occupational exposure limits. Suitable washing facilities should be available in the work area.
Individual protection measures, s	uch as personal protective equipment
Eye/Face Protection	Wear safety goggles and face shield where splashing is possible.
Skin and Body Protection	Wear impervious gloves such as butyl rubber, nitrile, neoprene, polyethylene, polyvinyl chloride or Viton. Follow instructions for Category C on an EPA resistance category selection chart for more options. Wear long-sleeve shirts, long pants, socks and shoes when using this product.
Respiratory Protection	In operations where exposure levels are exceeded, a NIOSH approved respirator with methylamine or organic vapor cartridges with approved pesticide prefilter or supplied air respirator appropriate for the form and concentration of the contaminants should be used. Selection and use of respiratory equipment must be in accordance with OSHA 1910.134 and good industrial hygiene practice. Refer to the product label for additionalinformation.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

## Information on basic physical and chemical properties

Physical state Appearance	Liquid Dark, green liquid	Odor	Pungent, petroleum distillate
Color	Dark green	Odor Threshold	Not determined
Property pH Melting point / freezing point Boiling point / boiling range Flash point Evaporation Rate Flammability (Solid, Gas) Flammability Limit in Air Upper flammability or explosive limits	Values_ N/A Not determined 149 °C / 300.2 °F >38 °C / >100.4 °F Not determined Liquid-Not applicable Not determined	<u>Remarks • Method</u>	
Lower flammability or explosive limits	Not determined		
Vapor Pressure	Negligible Not determined		
Vapor Density Relative Density	0.97-1.00		
Water Solubility	Insoluble in water		
Solubility in other solvents Partition Coefficient Autoignition temperature Decomposition temperature Kinematic viscosity Dynamic Viscosity Explosive Properties Oxidizing Properties	Soluble in hydrocarbon solvents Not determined Not determined Not determined Not determined Not determined Not determined Not determined		

Other information VOC Content (%)

<35%

# **10. STABILITY AND REACTIVITY**

#### Reactivity

Not reactive under normal conditions.

# Chemical stability

Stable under recommended storage conditions.

#### Possibility of hazardous reactions None known.

#### Conditions to Avoid None known.

# Incompatible materials

Oxidizers.

## Hazardous decomposition products

When heated to decomposition emits carbon monoxide, carbon dioxide and inorganic copper.

# **11. TOXICOLOGICAL INFORMATION**

## Information on likely routes of exposure

Product Information	
Eye Contact	May cause irritation with redness and tearing.
Skin Contact	May be harmful in contact with skin. May cause skin irritation with redness and pain.
Inhalation	Inhalation of mists may cause irritation of vapors may cause central nervous system effects, dizziness, drowsiness, somnolence, convulsions, tremors, light-headedness, loss of consciousness, impairment of short-term memory, loss of coordination, personality changes, headache, fatigue, stupor and coma.
Ingestion	May be harmful if swallowed. Ingestion of copper salts may produce vomiting, metallic taste, headache, cold sweats, shock, jaundice, swollen liver, kidney damage, CNS depression and death from CNS depression or liver or kidney failure. Whether such effects occur following copper naphthenate ingestion is unknown.

# **Component Information**

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Copper naphthenate 1338-02-9	= 2 g/kg (Rat)	> 2000 mg/kg (Rabbit)	-
Mineral Spirits 8052-41-3	-	> 3000 mg/kg (Rabbit)	-

# Symptoms related to the physical, chemical and toxicological characteristics

Symptoms	Please see se	Please see section 4 of this SDS for symptoms.			
Delayed and immediate effects	s as well as chronic	effects from short and le	ong-term exposure		
Sensitization	This material	This material is not known to cause sensitization.			
Germ cell mutagenicity	Not expected	Not expected to cause germ cell mutagenicity.			
Carcinogenicity		Chronic exposure to copper salts has produced lung and liver damage which sometimes progressed to cancer.			
Chemical name	ACGIH	IARC	NTP	OSHA	
Copper naphthenate 1338-02-9		Group 2A		X	
Reproductive toxicity	Not expected	Not expected to cause reproductive toxicity.			
STOT - repeated exposure	Causes dama	Causes damage to organs through prolonged or repeated exposure.			
Chronic toxicity	Mav cause da	May cause damage to the blood, kidneys, nervous system, and peripheral nervous system. Prolonged skin contact may cause defatting, drying, skin ulcers, or pruritic eczema. Prolonged inhalation can affect behavior and central nervous system as described under inhalation.			

# Aspiration hazard May be fatal if swallowed and enters airways.

# Numerical measures of toxicity

Not available.

# **12. ECOLOGICAL INFORMATION**

# **Ecotoxicity**

Very toxic to aquatic life with long lasting effects.

# **Component Information**

Not available

## Persistence/Degradability

Not determined.

# **Bioaccumulation**

There is no data for this product.

#### Mobility

Not determined

## Other Adverse Effects

Not determined

# **13. DISPOSAL CONSIDERATIONS**

#### Waste Treatment Methods

Disposal of Wastes	Disposal should be in accordance with applicable regional, national and local laws and regulations.
Contaminated Packaging	Disposal should be in accordance with applicable regional, national and local laws and regulations.

#### California Hazardous Waste Status

Chemical name	California Hazardous Waste Status
Copper naphthenate	Toxic
1338-02-9	

# **14. TRANSPORT INFORMATION**

<u>Note</u>	Please see current shipping paper for most up to date shipping information, including exemptions and special circumstances.
DOT UN/ID No Proper Shipping Name Hazard class Packing Group Marine Pollutant	Not regulated if shipped in NON BULK packaging (single containers less than 119 gal/ 882 lbs) by ground transport BULK Packaging (single containers larger than 119 gal/ 882 lbs): UN1993 Flammable liquid, n.o.s. (Copper naphthenate, mineral spirits) 3 III This material ships as a marine pollutant when inner package/single container is greater than 119 gallons. (Copper naphthenate).
IATA UN number Proper Shipping Name Transport hazard class(es) Packing Group	UN1993 Flammable liquid, n.o.s. (Copper naphthenate, mineral spirits) 3 III

IMDG	
UN number	UN1993
Proper Shipping Name	Flammable liquid, n.o.s. (Copper naphthenate, mineral spirits)
Transport hazard class(es)	3
Packing Group	III
Marine Pollutant	Yes (Copper naphthenate)

# 15. REGULATORY INFORMATION

## International Inventories

Chemical name	TSCA	<b>TSCA</b> Inventory	DSL/NDSL		ENCS	IECSC	KECL	PICCS	AICS
		Status		NCS					
Copper naphthenate	Х	ACTIVE	Х	Х	Х	Х	Х	Х	Х
Mineral Spirits	Х	ACTIVE	Х	Х		Х	Х	Х	Х

#### Legend:

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

# US Federal Regulations

# <u>CERCLA</u>

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355).

#### SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Hazard	No
Fire Hazard	No
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

## <u>SARA 313</u>

Chemical name	CAS No	Weight-%	SARA 313 - Threshold Values %
Copper naphthenate - 1338-02-9	1338-02-9	60-80	1.0

# CWA (Clean Water Act)

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Copper naphthenate		Х		

#### US State Regulations

## California Proposition 65

This product does not contain any Proposition 65 chemicals.

#### U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
Copper naphthenate 1338-02-9	Х		Х
Mineral Spirits	Х	Х	Х
8052-41-3			

#### EPA Pesticide Registration Number EPA Reg. No. 64405-17

#### **EPA Statement**

This chemical is a pesticide product registered by the Environmental Protection Agency and is subject to certain labeling requirements under federal pesticide law. These requirements differ from the classification criteria and hazard information required for safety data sheets, and for workplace labels of non-pesticide chemicals. Following is the hazard information as required on the pesticide label:

#### EPA Pesticide Label

Please refer to EPA label for additional information

#### Difference between SDS and EPA pesticide label

Please refer to EPA label for additional information

# **16. OTHER INFORMATION**

<u>NFPA</u> HMIS	Health Hazards 1 Health Hazards 1	Flammability 2 Flammability 2	Instability 0 Physical hazards 0	Special Hazards Not determined Personal Protection Not determined
Issue Date: Revision Date:	03-Jun-2 05-May-			

SDS sections updated

#### Disclaimer

**Revision Note:** 

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

