



**NISUS CORPORATION**  
**BORA-CARE® WARRANTY MANAGEMENT SYSTEM**  
**Bora-Care Technician Exam Instructions**

To become an authorized Bora-Care technician, you must pass the examination. To prepare for it, simply:

1. Read the [Bora-Care New Construction Technical Bulletin](#)
2. Read the [Bora-Care Specimen Label](#)
3. Watch the [training video](#)

Once you review these materials, enter your information below and take the test. Instructions on where to send this page along with your completed test for review are at the end.

Once you pass, you will be e-mailed a Bora-Care Authorized Technician Certificate. Technicians are required to refresh their training and take the test **every two years**. If you do not pass, you will be shown which answers are incorrect and will have the opportunity to re-take the exam.

**Date:**

**Technician's First Name:**

**Last Name:**

**Technician's Email Address:**

**Pest Company Name:**

**Pest Company Branch Address:**

**State:**

**Zip:**



1. What is the active ingredient in BORA-CARE?

- |                 |                                  |
|-----------------|----------------------------------|
| Orthoboric Acid | Disodium Octaborate Tetrahydrate |
| Chlorpyrifos    | Glycol                           |

2. BORA-CARE can be sprayed on plants and crops.

- |     |    |
|-----|----|
| Yes | No |
|-----|----|

3. BORA-CARE should be applied only to bare wood, plywood, particle board and other wood composite materials where an intact water repellent barrier such as paint, stain, or a sealer is not present.

- |     |    |
|-----|----|
| Yes | No |
|-----|----|

4. What solution ratio must be used when using BORA-CARE as a pretreatment for subterranean termites?

- |                                   |                                   |
|-----------------------------------|-----------------------------------|
| 1 part water to 1 part BORA-CARE  | 2 parts water to 1 part BORA-CARE |
| 1 part water to 5 parts BORA-CARE | 5 parts water to 1 part BORA-CARE |

5. BORA-CARE is labeled as a primary pretreatment for the control of subterranean termites.

- |     |    |
|-----|----|
| Yes | No |
|-----|----|

6. Apply one gallon of BORA-CARE (1:1) solution to point of wetness in a \_\_\_\_\_ wide uninterrupted horizontal band to all wood surfaces in crawl spaces and basements, to include all sills, plates, floor joists, piers, girders and subfloors as well as wood exposed to vertical access from the soil. (such as support piers)

- |        |         |
|--------|---------|
| 6 inch | 12 inch |
| 8 inch | 24 inch |

7. According to label instructions a structural pretreatment with BORA-CARE is best performed when greatest access to all wood members is available.

- |     |    |
|-----|----|
| Yes | No |
|-----|----|

8. Pretreatment to buildings on slabs requires applying a \_\_\_\_\_ BORA-CARE solution to all base plates and the bottom 24 inches of all studs on all exterior and interior walls and slab penetrations.

- |   |   |
|---|---|
| 5:1 (5 parts water to 1 part BORA-CARE) | 2:1 (2 parts water to 1 part BORA-CARE) |
| 3:1 (3 parts water to 1 part BORA-CARE) | 1:1 (1 part water to 1 part BORA-CARE)  |

9. On wood where access is limited to one or two sides of wood members such as sill plates on foundation walls, apply two coats of BORA-CARE solution waiting at least 20 minutes between applications.

Yes No

10. BORA-CARE is labeled to protect wood from the following wood destroying organism(s).

Subterranean Termites Drywood Termites  
Powderpost Beetles Wood Decay Fungus  
All the above

11. Applicators of BORA-CARE® must wear a long-sleeve shirt and long pants, socks, shoes, chemical resistant gloves and protective eyewear and a NIOSH approved respirator is recommended in confined areas.

Yes No

12. Tests in Gulfport, MS have shown that BORA-CARE protected treated wood from termite damage and tubing for twelve years.

True False

13. One gallon of BORA-CARE (1:1) solution will treat 400 square feet of exterior wood sheathing.

True False

14. If other termite control products are used in conjunction with the BORA-CARE pretreatment application they must be listed on the Residential New Construction Registration Form.

True False

15. According to documentation on the Residential New Construction Registration Form pretreatment applications of BORA-CARE can be applied to wood in contact with what type of structure.

Slab Crawl  
Basement Combination

All the above

16. Square Footage measurements of the property must be listed on the Residential New Construction Registration Form.

True False

17. According to the BORA-CARE New Construction Technical Bulletin, JECTA® may be injected into I-beams four or more inches thick at the point they come into contact with crawlspace or basement foundations and support piers.

True False

18. Linear footage measurements of what areas must be listed for slab construction on the Residential New Construction Registration Form.

Exterior Stud Walls

Interior Stud Walls

Exterior Wood Sheathing

All the above

**E-MAIL YOUR COMPLETED TEST TO:**

[info@nisuscorp.com](mailto:info@nisuscorp.com)

**SUBJECT:** Attn: Bora-Care Warranty

